



## VERTICAL MOUNT PL LAMPS



### G23 - 2 pin base wiring



### G24q - 4 pin base wiring



### APPLICATIONS

- Recessed cans
- Sconce fixtures



### PRODUCT SPECIFICATIONS

WATTAGES	6W, 8W, 11W
COLOR TEMPS	30K, 40K
EFFICACY	95-110 lm/W
LUMENS	6W - 620; 8W - 850; 11W - 1,270
INPUT VOLTAGE	120/277V
CRI	>80
BASE TYPE	G23, GX23, G24d, G24q, GX24q, GU24
DIMENSIONS	2.20" x 4.70"
SUGGESTED HID EQUIV.	6W - 13W; 8W - 18W; 11W - 26W
LISTED	UL
WARRANTY	3 year



**READ BEFORE INSTALLATION:** IN ORDER TO USE THIS PL REPLACEMENT LAMP, THE BALLAST MUST BE BYPASSED AND FIXTURE REWIRED ACCORDING TO THE DIAGRAM BELOW. 110-277V LINE AND NEUTRAL MUST BE CONNECTED TO OPPOSITE PINS OF LAMP. IF ANY QUESTIONS OR CONCERNS, CALL (800) 679-9243 BEFORE INSTALLING. IF INSTALLED WITHOUT BYPASSING THE BALLAST, THIS LAMP WILL BE DESTROYED. NOT FOR USE FOR DIMMERS

### PRODUCT BUILDER

ex: PL-G23-6-40K-V

TYPE	BASE	WATTAGE	COLOR TEMP	MOUNT
PL				V=Vertical
	G23 GX23 G24d G24q GX24q GU24	6=6W 8=8W 11=11W	40K=4000K 30K=3000K	

#### Base Types

