

LOADING DOCK LED LIGHT WITH WATTAGE AND CCT SELECTABLE



Adjustable Angle



APPLICATIONS

Industrial Loading Docks, Warehouse Interiors, Distribution Centers, Manufacturing Facilities, Cold Storage & Food Distribution, Maintenance Bays & Service Areas, Enclosed Trailers & Docking Stations.



PRODUCT SPECIFICATIONS

WATTAGE	30/50W selectable
COLOR TEMP	30/40/50K selectable
INPUT VOLTAGE	120/277VAC
OPERATING TEMP	-40 to 45°C (-40°F to 113°F)
LUMENS	30W- 3,900; 50W- 6,500
EFFICACY	130 lm/W
LED LIFESPAN (L70)	50,000 hours
CRI	>80
BEAM ANGLE	120 degrees
WEIGHT	4.23 lbs
DOCK LIGHT	Rotates 360 degrees
MOUNTING	2 Pole Wall Mount
WARRANTY	5 year
LISTED	ETL
RATED	IP65
OPERATING TEMP	-40°C to +45°C (-40°F to +113°F)
WORKING TEMP	-4°F to 104°F
HOUSING	Die Cast Aluminum
LENS	Clear Glass
3.28 FT CORD	Hidden wire design for safety

Notes: Built-in heat dissipation – always cool to the touch 45 in. Double swing flexible arm for directing light. Industrial-Grade heavy-duty die-cast aluminum for non-corrosive environments.

PART NUMBER	ZL-BB-GKD-30/50W
--------------------	-------------------------

LOADING DOCK LED LIGHT WITH WATTAGE AND CCT SELECTABLE

DIMENSIONS

