

MADE IN AMERICA

OUTDOOR SIGN LIGHT



CONSTRUCTION:

Housing is made of heavy gauge extruded aluminum with die cast end plates and splice box fittings. Housing interior is finished in a baked enamel finish for maximum reflectivity and durability. Splice box is threaded for 3/4" conduit and contains adjusting screws for housing. Lens is clear smooth slide-on acrylic that resists yellowing.

ELECTRICAL:

Housing is UL Certified damp and wet location.

MOUNTING:

Units are designed to be conduit mounted either individually, tandem, or in a continuous run


WARRANTY & LISTINGS:

- 5 year warranty of all electronics and housing
- UL Certified for wet location on housing only



This sign unit provides high light levels with even distribution, for spot lighting. The unit is weather resistant and suitable for most outdoor applications.

DIMENSIONS:



Fixture Length
53"
101"



HIGH OUTPUT PRODUCT BUILDER

PRODUCT #	SIZE	COLOR TEMP	# OF BARS	BAR LENS	WATTAGE
ZL-OD-LED	4=4FT 8=8FT	40K 50K	4ft 1 8ft 2	CL=Clear Blank=None	4ft 60W 8ft 120W

**MADE IN
AMERICA**

OUTDOOR SIGN LIGHT

LUMENS

Wattage 4ft = 1x 60W Driver	Wattage	Lumens With Lens	Lumens Without Lens
Driver Settings Below 1x60W Driver		165	175
62 Watts	62	10,230	10,850
60 Watts	60	9,900	10,500
57 Watts	57	9,405	9,975
55 Watts	55	9,075	9,625
50 Watts	50	8,250	8,750
45 Watts	45	7,425	7,875
40 Watts	40	6,600	7,000

Wattage 8ft = 2x60W Drivers	Wattage	Lumens With Lens	Lumens Without Lens
Drivers Settings Below 2x60W Driver		165	175
124 Watts 2x62W Drivers	124	20,460	21,700
120 Watts 2x 60W Drivers	120	19,800	21,000
114 Watts 2x 57W Drivers	114	18,810	19,950
110 Watts 2x55 Watt Drivers	110	18,150	19,250
100 Watt 2x50 Watt Drivers	100	16,500	17,500
90 Watts 2x45 Watt Drivers	90	18,150	15,750
80 Watts 2x40 Watt Drivers	80	13,200	14,000